SENSEI project

Sub-Electron-Noise SkipperCCD Experimental Instrument


Ultra low-energy threshold detectors for light DM

Javier Tiffenberg[†]

December 6, 2016


† Fermi National Laboratory






capacitance of the system is set by the SN: C=0.05pF ightarrow 3μ V/e






Accumulate the charge in the SW and reset the SN voltage $\,$






Disconnect the SN so it's floating. Measure the baseline voltage in the SN.






Move the change to the SN and measure the shift in the voltage










excellent for removing high frequency noise but sensitive to low frequencies




Readout noise: empty pixels distribution





Lowering the noise: Skipper CCD


- Main difference: the Skipper CCD allows multiple sampling of the same pixel without corrupting the charge packet.
- The final pixel value is the average of the samples Pixel value = $\frac{1}{N}\Sigma_i^N$ (pixel sample)_i





Lowering the noise: Skipper CCD

- Main difference: the Skipper CCD allows multiple sampling of the same pixel without corrupting the charge packet.
- The final pixel value is the average of the samples Pixel value = $\frac{1}{N}\Sigma_i^N$ (pixel sample);





This instrument already exist: SENSEI








Image taken with SENSEI






Charge in pixel distribution. Counting electrons: 0, 1, 2...






Charge in pixel distribution. Counting electrons: 0, 1, 2...






Counting electrons: ..38, 39, 40...







Counting electrons: ..38, 39, 40...















keep counting: ..1575, 1576, 1577...





Noise vs. #samples - $1/\sqrt{N}$





Skipper CCD: Operation mode

- Counting electrons ⇒ **noise has zero impact**
- It can take about 1h to readout a 4kx4k sensor
- Dark Current is the limiting factor

It's better to readout continuously to minimize the impact of the DC


	Number of DC events (100 g y)	
Thr /e	$DC = 1 imes 10^{-3} \; e \; pix^{-1} day^{-1}$	$DC = 10^{-7} e pix^{-1} day^{-1}$
1	1×10 ⁸	1×10 ⁴
2	2×10 ⁴	2×10 ⁻⁵
3	3×10 ⁻²	3×10^{-14}

Measured upper limit for the DC in CCDs is 1×10^{-3} e pix⁻¹day⁻¹. Could be orders of magnitude lower. Theoretical prediction is $O(10^{-7})$.



Skipper CCD - electron recoil reach


Electron recoil sensitivity computed by LDRD collaborators: Rouven Essig, Jeremy Mardon, Tomer Volansky, Tien-Tien Yu.





From yesterday's Agency-Perspective talks

[..] HEP is interested in identifying new, small project(s), for dark matter searches in areas of parameter space (i.e. mass ranges or types of particles) not currently being explored.





SENSEI is the ultimate silicon ionization detector Dream sensor for electron recoil channel



SENSEI and **Skipper-CCD** detectors prospects

SENSEI is the ultimate silicon ionization detector Unmatched performance for electron recoil channels

- Probe DM masses at the MeV scale through electron recoil.
- Probe axion and hidden-photon DM with masses down to 1 eV.
- Probe DM masses as low as 0.1 GeV through nuclear recoil.
- ullet Push boundaries of coherent u-nucleus interaction experiments.

Participants

- Fermilab: Javier Tiffenberg, Yann Guardincerri, Miguel Sofo Haro
- LBNL: Steve Holland, Christopher Bebek
- Stony Brook: Rouven Essig


- Tel Aviv University: Tomer Volansky
- CERN: Tien-Tien Yu
- Stanford University*: Jeremy Mardon



BACK UP SLIDES



CCD: readout - typical operation for DM searches




- The number of **real** events (produced by particles) scales with the total exposure time.
- The number of **fake** events (product of readout noise) scale with the number of readings (images taken).

It is better to read as few times as possible.



Electron density-of-states (1509.1598)





Whats next: Installation @MINOS & low radiation package

